CXL 108-185C

Unity Gain, Broad-Band Base Station and Marine Antenna for 108 - $185\ \text{MHz}$

DESCRIPTION

- CXL 108-185C is a 0 dBi gain, omnidirectional base station and marine antenna.
- The antenna is extremely broad-banded and covers the complete band: 108 – 185 MHz.
- CXL 108-185C is designed for fixation on supporting tubes with outer diameter between 27 mm and 65 mm.
- The construction of the mount makes it possible to lead the cable either inside or along the outside of the mast tube.
- A glass fibre tube completely encloses the carefully designed radiating element to ensure long dependable service in all climates.
- Atmospherical discharges are immediately led to ground as all metal parts are DC-grounded (consequently, the antenna shows a DC-short across the coaxial cable).
- This antenna is used where reliability is of utmost importance. A long lifetime has been taken into consideration when designing this antenna – it is sturdy and strong.




ORDERING DESIGNATIONS

TYPE	PRODUCT NO.
CXL 108-185C	100000513

SPECIFICATIONS

CXL 108-185C
Coaxial, broad-band dipole
Covering: 108 – 185 MHz
Nom. 50 Ω
Omnidirectional
Vertical
0 dBi
77 MHz
≤ 2.5
50 W continuous for 20 min. @ Duty cycle 50 %
All metal parts DC-grounded (Connector shows a DC-short)
-30° C → +70° C
N-female
0.062 m ² / 0.67 feet ²
73 N @ 160 km/h / 99.42 mph.
Marine white
Radome : Polyurethane-coated glass fibre Mounting bracket: Seawater resistant aluminium, epoxy-coated
Approx. 1.64 m / 64.57 in.
Approx. 1.64 m / 64.57 in. Approx. 3.5 kg / 7.72 lb.

MULTI-PURPOSE MOUNTING BRACKET







TYPICAL SWR CURVE

CHI/S11 SWR 0.5/Div CAL 6.00 5.50 4.50 4.00 3.50 2.50 2.00 1.50 50.000 MHz 20.0000 MHz/Div 250.000 MHz


TYPICAL GAIN CURVE



TYPICAL RADIATION PATTERN (E-PLANE)



TYPICAL RADIATION PATTERN (H-PLANE)





PROCOM A/S reserve the right to amend specifications without prior notice.

23/05/14

